

**Feature** 



**Benefit** 


## MR HH325 VP EU

**Unit Specifications** 

| 1.3 or 5 Watts                          | Adjustable output power for short and long communication.  | General                            |                |  |
|---|--|------------------------------------|----------------|--|
| 7                                       | Allows operation on any of the three (3) different channel maps established  | Number of Channels                 |                | All International, Canadian, U.S.A.,   |
| International, Canada & U.S.A. Channels | for these areas.   | Channel Spacing                    |                | 25 kHZ   |
| External Speaker/Microphone Jack        | Connect Cobra speaker mic accessories for hip or body worn operation.  | Modulation                         |                | 5 kHz Max.   |
| Instant Channel 16                      | Instant access to channel 16 for emergency situations.   | Input Voltage Battery Life: 5:5    | :90 Stand-by   | 7.2 VDC  |
| Unlimited Channel Memory                | Allows programming of unlimited channels for easy retrieval or scanning.   | Alkaline Battery                   |                | Included Battery 11 Hours @ 5 Watts 18.5 hours@ 1 Watt  Cobra® Battery Pack CM 110-009 |
| Tri-Watch                               | Monitors three (3) channels at once - Channel 16 and two (2) user selected channels.   |                                    |                |  |
| Scan                                    | Scan all channels to find conversations in progress.   | Current Drain:                     | Stand-by       | 40 mA  |
| Memory Scan                             | Scan channels programmed in memory to find conversations in progress.  |                                    | Receive        | 200 mA   |
| Signal Strength Meter                   | Shows the strength of the receiving and transmitting signal.   |                                    | Transmit       | 1.8 A @ High Power<br>700 mA @ Low Power   |
| Button/Key Lock                         | Locks function buttons/keys to eliminate accidental change of settings.  | Temperature Range                  |                | -20°C to 50°C  |
| Battery Tray With Charge Contacts       | Allows charging of batteries by simply dropping in the cradle.   | Unit Dimensions                    |                | 4.8" x 2.4" x 1.4"<br>(123 mm x 62 mm x 36 mm)<br>Not including antenna                |
| Illuminated Function Keys               | Allows high visibility of function keys.   | Unit Weight (Lbs)                  |                | 8 oz. (228 g)<br>Without batteries   |
| Illuminated LCD Display:Large           | Allows high visibiity of display. Up to 60% larger than the competition.   |                                    |                |  |
| Selectable Key Tone Beep                | Key press beeps can be turned off to silent operation.   | Receiver                           |                | 15/ 050 · 1/0 075 WI   |
| ATIS                                    | Capable of operating within the Automatic Transponder Indentification System. ATIS includes data at the end of a transmission for station identification.                      | Frequency Range<br>Receiver Type   | 9              | 156.050 to 163.275 MHz  Double Conversion Super-Heterodyn                              |
|   |  | Sensitivity:                       |                | Dooble Conversion Super-Helerouy   |
| Submersible                             | Meets JIS7 standards; Submersible for 30 minutes in one meter deep water.  | _                                  | 20 dB Quieting | 0.35 uV  |
|   |  |                                    | 12 dB Sinad    | 0.30 uV  |
| Included Accessories                    |  | Adjacent Channe                    |                | -60 dB   |
| 1500 mAh NiMH Rechargeable Battery      | Provides extended operating time compared to alkaline batteries with no memory effect.   | Intermodulation                    |                | -60 dB   |
| Locking Desktop Charger                 | Allows charging of batteries at home, car or boat. 12 volt vehicle adapter,<br>AC wall adapter and mounting hardware included. Installs on horizontal<br>or vertical surfaces. | Spurious & Image Rejection         |                | -60 dB   |
|   |  | AF Output                          |                | 250 mW @ 8 Ohms  |
|   |  | Transmitter                        |                | 156.025 to 157.425 MHz   |
| Spring Loaded Swiveling Belt Clip       | Secures the radio while on the go. Also removable.   | Frequency Range<br>RF Output Power |                | 1, 3 or 5 Watts  |
| Wrist Strap                             | For ease of carrying and securing while on the go.   | Spurious Emissio                   |                | -60 dB @ High Power<br>-55 dB @ Low Power  |
|   |  | Frequency Stabil                   | ity            | +/-10 ppm  |
|   |  | FM Hum & Noise                     | )              | 40 dB  |
|   |  | Packaging !                        | Specifications |  |
|   |  | Individual Clam/                   | Box Dimensions | 14.0" H x 8.9" W x 3.3" D<br>(356 mm x 226 mm x 84 mm)                                 |
|   |  | Individual Clam/                   | Box Weight     | 2 lbs., 2 oz. (964 g)  |
|   |  | Master Pack Qty.                   |                | 4  |
|   |  |                                    |                | 7.0" H x 22.0" W x 9.1" D  |

Cobra®, CobraMarine®, Nothing Comes Close to a Cobra® and the snake design are registered trademarks of Cobra Electronics Corporation, USA. Cobra Electronics Corporation, USA.

Features and specifications subject to change.



7.0" H x 22.0" W x 9.1" D

8 lbs., 12 oz. (3969 g)

MR HH325 VP EU 0 28377 20107 3

1 0028377 20107 0

(178 mm x 559 mm x 231mm)

Master Pack Dimensions

Master Pack Weight

Master Pack Barcode

SKU#

UPC#