## MARINE VHF TRANSCEIVER COLOTICA NIARRES RINES



PRESET BUTTON -SAVE YOUR FAVORITE CHANNELS!



COBRA® UNIQUE
REWIND-SAY-AGAIN™
FEATURE
(MISS A CALL? PLAY IT BACK
BY PUSHING ONE KEY)



LONGER TALK TIMES!



SELECTABLE POWER OUTPUT-1, 3 or 5 WATTS

Cobra Marine® Professional Series MR HH415 LI VP EU Features:

- Unique Compact Design
- Submersible to JIS7 Standards
- Tri-Watch
- Unlimited Channel Memory
- External Speaker/Mic Jack
- Selectable Power Output -1, 3 or 5 Watts
- Large Illuminated Display
- Signal Strength Meter (Transmit and Receive Signal Bars)
- Illuminated Function Keys
- Instant Channel 16
- Spring Loaded Belt Clip
- ATIS







RAPID CHARGER & ACCESSORIES INCLUDED

**ACTUAL SIZE** 

MR HH415 LI VP EU



## MR HH415 LI VP EU

Feature	Benefit	Unit Specifications
1.3 or 5 Watts	Adjustable output power for short and long communication.	General
	Allows operation on any of the three (3) different channel maps established	Number of Channels
International, Canada & U.S.A. Channels	for these areas.	Channel Spacing
Cobra® Exclusive Rewind-Say-Again™ Feature	Not quite sure if the call was for you? Push the REWIND key to play back up to the last 20 seconds of audio. Other bonus recording features included.	Modulation Input Voltage
LiON Polymer Battery	Lithium-Ion Polymer Battery allows for longer talk times, more successful charging seasons and maintenance free operation.	Battery Life: 5:5:90 Stand-by Alkaline Battery
External Speaker/Microphone Jack	Connect Cobra speaker mic accessories for hip or body worn operation.	20 Hours@ 5 Wat 35 Hours @ 1 Wa
Instant Channel 16	Instant access to channel 16 for emergency situations.	Battery Requirements
Unlimited Channel Memory	Allows programming of unlimited channels for easy retrieval or scanning.	Current Drain: Stand-by
Tri-Watch	Monitors three (3) channels at once - Channel 16 and two (2) user selected channels.	Receive Transmit
Scan	Scan all channels to find conversations in progress.	Temperature Range
Memory Scan	Scan channels programmed in memory to find conversations in progress.	Unit Dimensions
Signal Strength Meter	Shows the strength of the receiving and transmitting signal.	
Button/Key Lock	Locks function buttons/keys to eliminate accidental change of settings.	Unit Weight (Lbs)
Battery Tray With Charge Contacts	Allows charging of batteries by simply dropping in the cradle.	Receiver
Illuminated Function Keys	Allows high visibility of function keys.	Frequency Range Receiver Type
Illuminated LCD Display:Large	Allows high visibility of display. Up to 60% larger than the competition.	Sensitivity:
Selectable Key Tone Beep	Key press beeps can be turned off to silent operation.	20 dB Quieting
Battery Saver Circuitry	A unique circuit extends the life of the batteries. If there are no transmissions within 10 seconds, the unit will automatically switch to battery saver mode.	12 dB Sinad Adjacent Channel Selectivity
10 Selectable Call Tones	Allows the user to differentiate between up to 10 different parties on incoming calls.	Intermodulation and Rejection
Roger Beep Tone (selectable)	Confirmation tone indicates the completion of the user's transmission, and signals to others it is clear to talk. This feature is selectable and can be turned on or off. The detault is off.	Spurious & Image Rejection  AF Output
Patented VibrAlert®	Provides a silent alert for incoming calls. Ideal for noisy or all-quiet environments.	Transmitter
Submersible	Meets JIS7 standards; Submersible for 30 minutes in one meter deep water.	Frequency Range RF Output Power
Included Accessories		Spurious Emissions
AA Alkaline Battery Tray (CM 110-011)	Included with the 425 models. Allows using 6AA Alkaline Batteries to transmit in an emergency at full power. * Note - Some competitive models only allow for partial power transmit using Alkaline batteries.	Frequency Stability
		FM Hum & Noise
	• • • • • • • • • • • • • • • • • • • •	<b>Packaging Specification</b>
LiON Battery Pack (CM 110-010)	1900 mAh High Capacity Lithium-Ion Battery allows for longer talk times, more successful charging.	Individual Clam/Box Dimensions
Rapid-Charge Locking Desktop Charger	Allows charging of batteries at home, car or boat, 12 volt vehicle adapter, AC wall adapter	Individual Clam/Box Weight
(CM 110-008)	Allows charging of batteries at home, car or boat. 12 volt vehicle adapter, AC wall adapter and mounting hardware included. 3-4 Hour Charge. Vertical or horizontal mounting.	Master Pack Qty.
Swiveling Spring Loaded Belt Clip (CM 240-003)	Secures the radio while on the go. Commercial quality belt clip.	Master Pack Dimensions
Wrist Strap		Master Pack Weight SKU #
(CM 230-002)	For ease of carrying and securing while on the go.	UPC #
AC Adapter (CM 120-007)	220V AC Mains Adapter with EU and UK plugs. Allows for charging at home or on AC equipped boats.	Master Pack Barcode
DC Adapter (CM 130-002)	12V Accessory Port Adapter. Allows for charging on the DC system of smaller boats.	
• • • •		

<b>Unit Specif</b>	iculions	
General		
Number of Channels		All International, Canadian, U.S.A.,
Channel Spacing		25 kHZ
Modulation		5 kHz Max.
Input Voltage		7.2 VDC
Battery Life: 5:5:90 Stand-by Alkaline Battery		
	20 Hours@ 5 Watts	Included Battery 11 Hours @ 5 Watts
	35 Hours @ 1 Watt	18.5 hours@ 1 Watt
Battery Requirements		Cobra® Battery Pack CM 110-010
Current Drain:		
	Stand-by	40 mA
	Receive	200 mA
	Transmit	1.8 A @ High Power
Temperature Range		700 mA @ Low Power -20°C to 50°C
lemperature kange		4.8" x 2.4" x 1.4"
Unit Dimensions		(123 mm x 62 mm x 36 mm)
		Not including antenna
Unit Weight (Lbs)		8 oz. (228 g) Without batteries
Receiver		
Frequency Rang	е	156.050 to 163.275 MHz
Receiver Type		Double Conversion Super-Heterodyne
Sensitivity:		
	20 dB Quieting	0.35 uV
	12 dB Sinad	0.30 uV
Adjacent Channe	el Selectivity	-60 dB
Intermodulation and Rejection		-60 dB
Spurious & Image Rejection		-60 dB
AF Output		250 mW @ 8 Ohms
Transmitter		
Frequency Range		156.025 to 157.425 MHz
RF Output Power		1, 3 or 5 Watts
Spurious Emissions		-60 dB @ High Power -55 dB @ Low Power
Frequency Stability		+/-10 ppm
FM Hum & Noise		40 dB
Packaging	Specifications	
	Specifications  /Box Dimensions	14.0" H x 8.9" W x 3.3" D (356 mm x 226 mm x 84 mm)
Individual Clam,	/Box Dimensions	
Individual Clam, Individual Clam,	Box Dimensions  Box Weight	(356 mm x 226 mm x 84 mm)
Individual Clam, Individual Clam, Master Pack Qty	/Box Dimensions /Box Weight	(356 mm x 226 mm x 84 mm) 2 lbs., 2 oz. (964 g) 4 7.0" H x 22.0" W x 9.1" D
Individual Clam, Individual Clam, Master Pack Qty Master Pack Din	Box Dimensions  Box Weight  ensions	(356 mm x 226 mm x 84 mm) 2 lbs., 2 oz. (964 g) 4 7.0" H x 22.0" W x 9.1" D (178 mm x 559 mm x 231mm)
Individual Clam, Individual Clam, Master Pack Qty Master Pack Din Master Pack We	Box Dimensions  Box Weight  ensions	(356 mm x 226 mm x 84 mm) 2 lbs., 2 oz. (964 g) 4 7.0" H x 22.0" W x 9.1" D (178 mm x 559 mm x 231mm) 8 lbs., 12.0 oz. (3969 g)
Individual Clam, Individual Clam, Master Pack Qty Master Pack Din	Box Dimensions  Box Weight  ensions	(356 mm x 226 mm x 84 mm) 2 lbs., 2 oz. (964 g) 4 7.0" H x 22.0" W x 9.1" D (178 mm x 559 mm x 231mm)
Individual Clam, Individual Clam, Master Pack Qty Master Pack Din Master Pack We SKU #	/Box Dimensions /Box Weight nensions	(356 mm x 226 mm x 84 mm) 2 lbs., 2 oz. (964 g) 4 7.0" H x 22.0" W x 9.1" D (178 mm x 559 mm x 231 mm) 8 lbs., 12.0 oz. (3969 g) MR HH415LI VP EU

Cobra®, CobraMarine®, Nothing comes close to a Cobra® and the snake design are registered trademarks of Cobra Electronics Corporation, USA. Cobra Electronics Corporation™ and Rewind-Say-Again™ are trademarks of Cobra Electronics Corporation, USA.

Features and specifications subject to change.

©2007 CEEL, Dungar House, Northumberland Avenue, Dun Laoghaire, County Dublin, Ireland