



# IM-DVR-04

4 INPUT DIGITAL VIDEO RECORDER / WEB SERVER



**The New IM-DVR-04P Digital Video Recorder boasts a host of features that turn your on board cameras into a powerful security system.**

- 4 Composite Video Inputs / 1 Composite Video Output
- 4 Audio Channels
- Quad / Full Screen Display
- Realtime Live Display
- Event Recording, time-lapse recording or both
- Intelligent motion detection with programmable area & sensitivity
- Multi-Protocol PTZ Control
- SD Card / USB / Compact Flash ports for back-up of images and footage
- Alarm Inputs
- Configurable analogue contacts for control of auxiliary devices
- Ethernet connectivity for control of the internet
- Remote access for control over mobile phone or PDA
- Anti Vibration hard disk mounts
- GPS support
- Built in Heater

A stylish panel mountable Digital Video Recorder and Video Web Server with simple and intuitive front panel operation. The IM-DVR-04P is housed in a standard 1 DIN casing for easy installation and features shock proof mounts to prevent damage to the 2.5" SATA hard drive due to the vibration of the boats engines.

The IM-DVR-04P has been designed for mounting into the helm and can be installed externally when fitted in conjunction with the IM-DVR-04-COV fascia. The rear of the unit features serial data connections for PTZ devices, camera video and audio inputs (4 channels), composite and VGA monitor output and alarm inputs and user definatble contacts.

**Exclusive US Distribution:**

**SeaWide**  
DISTRIBUTION

**Iris Innovations Limited**


Sailmakers Loft, Kingscove Farm, Tanhouse Lane  
Botley, Hampshire SO30 2SZ  
Tel / Fax: +44(0)1489 798484  
email: [info@scubar.co.uk](mailto:info@scubar.co.uk)  
[www.boat-cameras.co.uk](http://www.boat-cameras.co.uk)



# IM-DVR-04

## Technical Information & Specifications

### REAR PANEL



### SPECIFICATIONS

Dimensions	178(W) x 210(D) x 50(H)mm
Weight	2.0 KG without 2.5" SATA HDD
Material	Lightweight aluminum casing, plastic fascia.
Operating System	Embedded Linux 2.6
Operation	Simultaneous record, live, playback, backup, control & Remote
Video System	PAL / NTSC
Video Inputs	4 CH BNC 1vP~P / 75Ω
Main Monitor	BNC x 1, S-Video, 1vP~P / 75Ω, Optional VGA D-SUB 15 connector
Loss Detection	Yes
Motion Detection	Yes - With configurable detection area & sensitivity
Audio	2 RCA Jack connectors, Line in level (100m V-2 Vrms) out (>2 Vrms)
Record Compression	Video - H.264 / Audio - ADPCM
Frame Rate (FPS) and Resolution	NTSC - 30 / 720*480, 60 / 720*240, 120 / 360*240 PAL - 25 / 720*576, 50 / 720*288, 100 / 360*288
Watermark	Yes
Network	1 RJ-45 10/100BaseT Ethernet
Web	Remote setup, backup, monitoring, alarm notification
Remote Stations	PC, mobile phone or PDA
Power Requirement	+12 or 24VDC, (tolerance +9.5 ~ 30VDC)
Consumption	12W Max without 12VDC output loading
Power Output	Up to 1A Max (for all cameras)
Operating Temperature	0°C ~ + 50°C / Built - in Heater

Exclusive US Distribution:



SeaWide Distribution SE Office

7137 24th Court East

Sarasota, Florida 34243

Tel: 866-732-9433

email: [sales@seawide.com](mailto:sales@seawide.com)

[www.seawide.com](http://www.seawide.com)