

PRODUCT OVERVIEW

VHF

The world's most advanced VHF with multi-station wireless touchscreen handsets.

AIS

Built-in Class B SOTDMA smartAIS with no-loss splitter.

MONITOR

Track and control, whether on board or ashore.





VHF Reimagined

Cortex is a revolution in marine technology that will change your VHF experience forever with an intuitive touchscreen engineered to withstand the rigours of the harsh marine environment.



The power of VHF and AIS combined

Cortex is the world's first VHF with high speed SOTDMA AIS transponder technology, making your boat visible to others. A built-in heading sensor tells other vessels your direction, helping them more accurately predict potential collisions. See critical information about vessels, AIS Aids to Navigation and man overboard devices on your MFD, mobile or Cortex handset.



Cortex continuously calculates collision risk and warns you with voice annunciated alerts. View crossing situations, navigation light sectors and perform trial maneuvers while talking on the VHF radio. Initiate direct calls (DSC) with other vessels by simply tapping the vessel on your handset touchscreen. Push to talk to quickly hail another vessel when every second counts.





Monitor

Cortex combines built-in sensors, external sensor inputs and NMEA 2000 connectivity with free basic monitoring. Using cloud connectivity, you can view twice-daily updates of power, location, wind, depth, bilge, temperature and more on your smartphone.

The Cortex Monitor Premium subscription unlocks real-time vessel status, instant alerts and device control for boat systems like refrigerators, icemakers, lights or heaters.

Anchor Watch on board and ashore

By combining your position and heading, Cortex will determine if your anchor drags. If your boat moves outside your anchor swing radius the alarm will sound on Cortex handsets, connected speaker and your smartphone. Receive alerts while ashore via the Cortex Monitor App on your smartphone.





CORTEX HUB

M1 & V1



Cortex M1 Hub is a Full Class B SOTDMA *smartAIS* with out-of-the-box monitoring. Cortex V1 combines Cortex M1 with Cortex H1 Tethered Handset to provide full VHF functionality. Optionally add H1P Portable Handsets for even greater freedom on board.

Cortex is the world's first VHF with high speed SOTDMA AIS transponder technology making your boat visible to others. A built-in heading sensor tells other vessels your direction, helping them more accurately predict potential collisions.

Configure and monitor the Cortex system and receive alerts to a connected smartphone on the Cortex Onboard App or receive alerts and control devices on the boat remotely using the Cortex Monitor App.


- Add H1 Tethered & H1P Portable handset for VHF capability
- · Built-in Class B SOTDMA
- Built-in antennas for WiFi and cloud connectivity for monitoring on board and ashore
- Transmit AIS and VHF simultaneously
- Universal compatibility
- Low power consumption
- Galvanically isolated ports


- Monitor up to 5 external sensors connected directly
- Network to NMEA 2000 to monitor sensors remotely or supported 3rd Party Apps
- Integrated no-loss AIS / VHF splitter
- IPx7 full plastic housing
- 10Hz GPS and external antenna port
- GNSS: GPS, GLONASS, Bei Dou, Galilleo
- · Anti jamming feature

TECHNICAL

- 1 VHF Antenna In
- 2 VHF Antenna Out (no-loss splitter)
- 3 DC Power (12/24V)
- 4 GPS/GNSS, WiFi and Cloud ports
- 5 Mounting holes
- 6 External Speaker output
- 7 General Purpose Input / Output, NMEA 0183
- 8 NMEA 2000 port
- 9 Coloured backlit status indicators for GPS/GNSS, VHF/AIS, WiFi, Cloud and Power







NOTE: Measurements based on metric



CORTEX ONBOARD APP

Configure and Monitor your Cortex system from your smartphone anywhere on board. Receive alerts for collision threats, anchor drags and more. **Android and iOS**



TETHERED & PORTABLE HANDSETS

H1 & H1P

The Cortex Handset is available in H1 Tethered and H1P Portable versions. Connect up to 10 Cortex Handsets to a Hub.

A revolution in marine technology that will change your VHF experience forever. An intuitive touchscreen that is engineered for durability to withstand the rigours of the harsh marine environment. Audio that's as loud as a train but clear as a bell. The future of VHF is here.

- Intuitive functionality
- Secure mounting and charging cradle
- One-touch DSC
- Single-handed operation with roary click-wheel
- Wireless freedom on board
- Up to 85 dBA audio

- Wide angle & sunlight viewable
- · Pinch-to-zoom
- · Critical data always in view
- Durability in wet and rough conditions
- · Gorilla Glass
- · Wet use touchscreen



TECHNICAL


- 1 DSC distress call button
- 2 Up to 85 dBA high fidelity speaker
- 3 Side volume buttons
- 4 Power On button
- 5 DSC Call shortcut
- 6 Channel 16 shortcut key
- 7 MOB waypoint activation
- 8 Click-wheel rotary controller
- в **Н1**



- 9 Microphone
- 10 VHF screen shortcut key
- 11 Return kev
- 12 Menu key
- 13 Push to talk key
- 14 4-inch touch screen
- 15 Protective rubber overmould
- 16 Power cord




HANDSET





CRADLE





CORTEX MONITORING


CORTEX MONITOR

Download the free Cortex Monitor App from Google Play or the App Store. Use your smartphone to monitor your vessel and receive alerts.

Know your vessel is safe and secure while you are ashore. See boat status, receive alerts and control devices. Cortex sends updates to the cloud and sends status and alerts directly to your mobile via the Monitor App.

- · Built into the Cortex Hub
- Free download with easy setup
- · Free out-of-the-box monitoring
- Add external sensors and controls
- Real-time monitoring and control via Premium Subscription
- In-App Upgrade to Cortex Monitor Premium Subscription
- · Monthly subscription cancel any time





CORTEX MONITOR PLANS

Download the free Cortex Monitor App from Google Play or the App Store. Annual & Monthly Subscription are purchased within the Cortex Monitor App.

WHAT YOU CAN MONITOR

- · Built-in monitoring:
- Battery voltage
- Barometric pressure
- Boat position
- · External sensor monitoring includes:
 - Bilge level
 - Bilge pump activation and cycles
 - Temperature
 - Security
- Wind indicator
- Water depth
- NMEA2000 network

FREE	PREMIUM		
Free	Monthly \$20 USD or Annual \$120 USD		
See twice daily updates on the Cortex Monitor App	See real-time updates on the Cortex Monitor App		
In-App Alarms	Instant alarm notifications		
	On board device control		
	Anchor Watch		
	Geofence		

GET MORE WITH PREMIUM

- Real-time updates on monitored sensors
- Instant push notifications for monitoring alarms to your smart phone
- Control of on board devices remotely
- smartAIS Anchor Watch for accurate anchor drag detection
- Geofence location alarms

COVERAGE:

Where you purchase Cortex determines monitoring coverage. Ensure you purchase the Cortex version that is correct for your region.

USA, Canada, Australia, New Zealand, Europe, United Kingdom

Rest of world & Roaming Contact us to find out more about additional coverage and roaming options.



SPECIFICATIONS

CORTEX HUB				
GENERAL SPECIFICATIONS				
HUB SIZE		168 x 168 x 58.7mm (6 5/8" x 6 5/8" x 2 5/16")		
POWER SUPPLY		9-33V. 12V: 6A max, 500mA nom		
WEIGHT		770g (1.7lb)		
ENVIRONMENTAL		Waterproof (IPx7)		
OPERATING TEMPERATURE		-25°C to +55°C (-13°F to +131°F)		
SUPPORTED PROTOCOLS		AIS Class B SOTDMA, VHF Voice, Class D DSC, ATIS (user configurable, EU region) NOAA Weather (US region)		
TRANSMITTER FREQUENCY ERROR		Less than 300Hz		
ANT CONNECTOR		S0239		
SPLITTER		Max input power 25W, Insertion Loss RX 0dB, TX < 1dB		
SPLITTER CONNECTOR		BNC		
VHF VOICE				
	TX RX	156.025-161.600 MHz 156.050-163.275 MHz		
DEDICATED RX CHANNELS		3		
POWER OUTPUT		25W, 1W (High, Low)		
REGIONS		USA, CAN, INT		
SENSITIVITY (12 DB SINAD)		-116 dBm		
ADJACENT CHANNEL SELECTIVITY		80 dB		
SPURIOUS RESPONSE		70 dB		
INTERMODULATION		70 dB		
SPURIOUS EMISSIONS		Less than -80 dBc (at 25 W)		
MAX AUDIO OUTPUT POWER		10W, < 1% THD		
CLASS D DSC				
DEDICATED RX CHANNELS		1		
SENSITIVITY (1% BER)		-113 dBm		
ADJACENT CHANNEL SELECTIVITY		80 dB		
SPURIOUS RESPONSE		70 dB		
INTERMODULATION		70 dB		
SOTDMA CLASS B AIS				
DEDICATED RX CHANNELS		2		
FREQUENCY RANGE		156.025 - 162.025 MHz		
POWER OUTPUT		5W, 1W (High, Low)		
AIS SENSITIVITY (20% PER)		-112 dBm		
ADJACENT CHANNEL SELECTIVITY		80 dB		
SPURIOUS RESPONSE		70 dB		
INTER-MODULATION		65 dB		
AUDIO				
SUPPORTED FUNCTIONS		VHF RX, Alarms		
AMPLIFIER		10W Class D, THD < 1%		
SPEAKER		4 ohm		

GNSS		
SENSITIVITY	-167dBm	
CONSTELLATIONS	GPS, GLONASS, Bei Dou, Galilleo	
CHANNELS	72	
DIFFERENTIAL SUPPORT	SBAS, WAAS, EGNOS	
NAVIGATION RATE	10Hz	
CONNECTOR	SMA	
CERTIFICATIONS	IEC 61108	
FEATURES	Anti-jamming, Anti-spoofing	
NETWORKING		
NMEA 2000 GATEWAY	1 x Isolated Micro-C male port, AIS, GPS & MOB PGN output, Gateway Translations to/from NMEA 0183	
NMEA 0183	1 x Isolated NMEA 0183 port, AIS and GPS sentences, Gateway Translations to/from NMEA 2000, 4800 / 38400 baud	
WIRELESS	Access Point for up to 10 devices, 2.4GHz, 802.11b/g/n, Integrated Antenna, SMA-RP external antenna port (optional)	
WIRELESS SECURITY	WPA2 Personal	
CLOUD CONNECTIVITY	LTE-Cat1 with 3G fallback (USA), 3G (Canada, EU, Asia), Integrated SIM, Integrated Antenna, SMA-RP external antenna port (optional)	
CONTROL OUTPUTS	2 Outputs, Low side driven (max 200mA)	
SENSORS		
HEADING	9-Axial, Internal use only, Accuracy: +/- 1 deg, Updated rate: 10Hz (max)	
BAROMETER	Update rate 1Hz max (averaged)	
BATTERY VOLTAGE	Measured at power input	
EXTERNAL SENSORS INPUTS	5 Inputs, Digital (0-24V), Analog (0-10V)	


CORTEX HANDSETS				
GENERAL SPECIFICATIONS				
HANDSET SIZE		164.8 x 71.8 x 21.4mm (6 1/2" x 2 13/16" x 7/8")		
POWER SUPPLY		12V, 1A max, 200mA nom 12-24V compatible		
BATTERY		Lithium Polymer 2 hour full charge, >12 hours nominal operation		
WEIGHT		H1 285g (0.63lb), H1P 235g (0.52lb)		
ENVIRONMENTAL		Waterproof (IPx7)		
OPERATING TEMPERATURE		-25°C to +55°C (-13°F to +131°F)		
AUDIO		3W Class D amplifier, THD < 5% @ 85dBA		
DISPLAY				
SCREEN	LCD TFT Si, 640 x 800, 24bit Colour			
TOUCH	Capacitive, optically bonded, LCD, glove and salt water operable			
BACKLIGHT	600 cd/m2, Ambient Light sensor for auto dimming			

All stated specifications are subject to change without notice or obligation. Dimensional measurements based on metric.



CORTEX RANGE







CORTEX V1 VHF WITH AIS		
PRODUCT CODE	CORTEX-V1	
UPC	0797776885848	
DESCRIPTION	VHF radio with SOTDMA smartAIS and remote vessel monitoring	
INCLUDED	M1 Hub, H1 Tethered Handset, GPS Antenna, Power Cable, NMEA 2000 Drop Cable, NMEA 2000 Tee, Audio Cable, External Sensors Cable, External WiFi Antenna.	
PACKAGING	330 x 218 x 148mm (1' 1" x 8 9/16" x 5 13/16") 1.98 kg (4.37 lb)	
MRP	\$1799 USD	



CORTEX H1P PORTABLE HANDSET		
PRODUCT CODE	CORTEX-H1P	
UPC	0735850824765	
DESCRIPTION	Cortex H1P Portable Rechargable Handset	
INCLUDED	H1P Portable Rechargable Handset, Charging H1P Cradle, Non Powered H1 Cradle	
PACKAGING	213 x 98 x 58 mm (8 3/8" x 3 7/8" x 2 5/16") 0.34 kg (0.75 lb)	
MRP	\$599 USD	

Compatible with Cortex M1 and V1 bundles.

ACCESSORY CODE	DESCRIPTION	CORTEX-M1	CORTEX-V1	CORTEX-H1	CORTEX-H1P
EXSPKR	EXTERNAL SPEAKER				
RAIL-H1P	RAILBLAZA MOUNT				
141005	SMART AIS ALARM & SWITCH KIT	Included			
NMEA-2M	NMEA 2000 DROP CABLE 2M (6' 6 3/4")	Included	Included		
NMEA-T	NMEA 2000 TEE	Included	Included		
CRDL-H1	NON-POWERED H1 CRADLE			Included	Included
CRDL-HIP	CHARGING H1P CRADLE (POWERED)				Included
PTC-VHF	M1 PATCH CABLE (BNC TO PL259 FOR SPLITTER)	Included			
PTC-GPS	GPS LOW LOSS PATCH CABLE, 10M (32' 9 11/16")	Included	Included		

This device is subject to FCC rules and will comply with the appropriate rules before delivery.







